

# Texture Stone Chip

Acrylic Stone Texture Coat-Exterior/Interior

## Spray Types for Decorative Texture Coats on Wall Surfaces.

**Powder/Chip of Marble, Granite, Natural Stone + Acrylic Resin for exterior/interior Wall. Excellent Color UV & High Performance of Fungus Resistance & Protection against Corrosion**

**Product Application:** **Texture Stone Chip**, is high-viscosity paste form acrylic resin adhesive & combined of Powder/Chip of marble, granite, natural stone contains. Offers excellent color UV, high hardness, fungus resistance and protection against corrosion. The texture coats has applied on wall system for high rise building, warehouses, garages, shopping centers, condominium, apartment & commercial etc.

**Advantage & Properties:** The specific advantage offered by solvent free coating & natural stones. Offers excellent color UV, high hardness, fungus resistance and protection against corrosion. Very good adhesion, the system recommended for cement wall, concrete can also be applied on other walls, mineral substrates, as stones, bricks, fibre-glass, metal surface or even tiles and glass.


**Ultraviolet Resistance:** **Not reflection to eye and no yellowing after 100 hours.**

- ❖ Adhesion is always good on mineral substrates surfacing.
- ❖ Very good mechanical properties following optimal cure.
- ❖ As elegant and durable as natural stone finish.
- ❖ Forms a hardness texture finish that is excellent of abrasion & scratch.
- ❖ Good in no dust from substrate coatings easy to clean, improved visibility.
- ❖ Excellent of fungus resistance, Good on hygienic wall surfacing.
- ❖ Adhesion promoting primers between old with new concrete.
- ❖ Non-toxic, the coatings have been cured applied on health floor.


### Available of Color



Code: GS 23  
**Texture Stone Chip**



Code: GS 27  
**Texture Stone Chip**



Code: GS 33  
**Texture Stone Chip**



Code: MS 51  
**Texture Stone Chip**



Code: MS 53  
**Texture Stone Chip**



Code: MS 55  
**Texture Stone Chip**



Code: MS 57  
**Texture Stone Chip**



Code: MS 59  
**Texture Stone Chip**

### Performance of Property Details

	<b>Texture Stone Chip Granite Type</b>	<b>Texture Stone Chip Marble Type</b>	<b>Texture Stone Chip Natural Stone Type</b>
<b>Specific Gravity:</b>	1.80-1.90gm/cm <sup>3</sup>	1.70-1.85gm/cm <sup>3</sup>	1.85-2.00gm/cm <sup>3</sup>
<b>Cure Time:</b>	120-180 mins	120-180 mins	120-180 mins
<b>Viscosity:</b>	130000 cps [±5000]	125000 cps [±5000]	135000 cps [±5000]
<b>Compressive Strength:</b>	18.50N/mm <sup>2</sup>	17.08N/mm <sup>2</sup>	19.50N/mm <sup>2</sup>
<b>Elongation at Break:</b>	2.50%	2.10%	2.50%

# Texture Stone Chip

## Acrylic Stone Texture Coat-Exterior/Interior

### Surface Preparation & Method Application

Surface to be repaired or sealed must be clean and sound. Concrete must be free of dust, sealers, grease and other bond inhibiting contaminants.

Concrete must cured at least 28 days and have with minimum Compressive Strength of 20 N/mm<sup>2</sup>. Those cement slurry, plaster droppings, etc. must be remove, the surface of concrete free of oil, grease, and other loose particles and contaminations.

**Texture Stone Chip**, it's easy to applied, there for using texture gun for Spray Equipment, application must be made in two proceed, first layer of Primer Coat & second layer coat of Texture Stone Chip [finish coat], **(Refer to Coverage Chart)**

**Optional**, if require of UV 100% system, is must applied clear coat "Gem Top Guard" for protection layer.

### Packing & Size:

5 kg, 10 kg, 20 kg or 25 kg pack

### Coverage Chart:

1<sup>st</sup> layer

#### Primer Coats layer

3-5/m<sup>2</sup> per kg

2<sup>nd</sup> layer

#### Texture Stone Chip

4.50-6.00 kg/m<sup>2</sup>  
depends on choice of powder/chip

### Optional layer for UV 100%

#### Gem Top Guard

3-4/m<sup>2</sup> per kg

### Mixing:

**Texture Stone Chip**, Supplied as two-component system. Mix materials with low speed drill and paddle for approximately two [2] minutes. Insure a thorough mix. Never mix more material than can be used in thirty (30) minutes. Do not apply Acrylic when ambient or surface temperatures are below 50 °F

### Storage

12 months from date of manufacture in original sealed container stored undercover 25 °C, at ambient temperature away from heat, and dry conditions. For clearing equipment, use special solvent liquid.

### Important 1:

While the information and data sheet contained in this promotional literature are presented in good faith and believed to be reliable, they do not constitute a part of our terms and conditions of sales unless specifically incorporated in our Order acknowledgement. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data sheet are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data sheet or products can be used without infringing patent of third parties.

### Important 2:

**LAMACO Malaysia** products are not guaranteed against defective materials and manufacture & are sold subject to its standard Terms & Conditions of sale, copies of which may be obtained on request. Whilst **LAMACO Malaysia** endeavors to ensure that any advice, recommendation, specification or information is accurate and correct, it cannot- because it has no direct or continuous control over where or how its products are applied - accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance any advice, specification, recommendation or information given by it.

### Health & Safety

Some of the components of this product may be hazardous during mixing and application. Please consult the relevant Health & Safety Data Sheets, available from **LAMACO Malaysia** on request and sent with each delivery.



## LAMACO SYSTEM SDN BHD

Co. No. 1033557-M

407, Jalan Perusahaan 6, Taman Bandar Baru Mergong,  
05150 Alor Setar, Kedah. Malaysia

Tel : +60-4-734 5555 Fax : +60-4-772 4444

Http : [www.lamaco.com](http://www.lamaco.com) Email : [info@lamaco.com](mailto:info@lamaco.com)



: +60 19 4486611 +60 19 4786611